

LOBADUR® 

Viva – Optimized formula

1K waterborne finish

Versatile and worldwide proven

Excellent for renovations and new installations!

LOBADUR® Viva, the worldwide proven universal talent among LOBA's single component waterborne finishes, has been successfully improved. Its optimized formula offers outstanding resistance to plasticizers from parquet adhesives and many other proven properties. This makes LOBADUR® Viva the ideal partner for both renovations and new installations of parquet and hardwood floors.

Optimized
formula



Why end users are convinced of Viva:

- Excellent resistance to household-related chemicals
- Long-lasting beauty of the floor due to high resistance to mechanical wear and line marks
- Very low emission and very low solvent content
- Time saving – fully durable after only 5 days

Why contractors are enthusiastic about Viva:

- Excellent processing properties – simple and safe, no lap marks
- Highly resistant to plasticizers from parquet adhesives
- Maximum safety for renovations and new installations
- Very low emission, EMICODE® EC1
- Low VOC content, GISCODE W2+

Special feature

LOBADUR® Viva is compatible with all Connected Systems approved parquet adhesives from Wakol. This gives you maximum security for renovations and new installations, as chemical reactions between finish and adhesive are eliminated.

More at www.loba.de/en/connected-systems



Range of use

1K waterborne finish for wood floors. For normal to heavy traffic in residential areas and light commercial use. Excellent for renovations and new installations.



Application

- To avoid side bonding it is recommended to use a primer (e.g. LOBADUR® WS EasyPrime)
- First coat of Viva with LOBATool Roller Deluxe 120 or Microfibre 100–120
- Recoating without intermediate sanding is possible within 24 hours
- Intermediate sanding after 8–10 hours at the earliest with LOBATool PerforatedPad P120 or finer; alternatively intermediate sanding with LOBATool Sanding net P120 or finer
- Second coat Viva with LOBATool Roller Deluxe 120 or Microfibre 100–120
- Consumption per coat: 100–120 ml/m²

Art.-no. 11519

Available in semi-gloss (1 l, 5 l, 10 l) and satin (5 l, 10 l)

GISCODE W2+

LOBA is always at your side and ensures your success with both advice and action. Our experienced experts are happy to support you individually with your projects. Our competent technical service team is at your disposal quickly, if you need hands-on assistance on site. You can always rely on us!

Please consider the detailed technical information, application advices and set-up recommendations.

Do you have any questions? Do not hesitate to contact us:

Technical Information



LOBA GmbH & Co. KG

Leonberger Str. 56–62 | 71254 Ditzingen | Germany | Fon: +49 7156 357-0 | Fax: +49 7156 357-211 | E-Mail: service@loba.de | www.loba.de/en