

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Product name** PrimaSeal Plus
- **Article number:** 11033-600000-000
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
LOBA GmbH
Leonberger Straße 56 - 62
D-71254 Ditzingen Tel.: +49 (0)7156/357-0
- United Kingdom:
Phi House
Southampton Science Park
Southampton, SO167NS
United Kingdom
Phone +442380766722
- **1.4 Emergency telephone number:**
Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

-
- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
 - **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
propan-2-ol
n-butyl acetate
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 1)

· Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable**· vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** Mixture of the substances listed below with harmless additions.**· Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	50-100%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	8.5-10%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures**· After inhalation** Supply fresh air; consult doctor in case of symptoms.**· After skin contact**

In general, the product is not irritating to the skin. Wash off the product with plenty of soap and water after skin contact.

· After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.**· After swallowing** In case of persistent symptoms consult doctor.**· 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**· 4.3 Indication of any immediate medical attention and special treatment needed** Symptom Treatment automatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media**· Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.**· For safety reasons unsuitable extinguishing agents**

Water.

Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Prevent material from reaching sewage system, holes and cellars.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep containers tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
Store in cool location.
Prevent any penetration into the ground.
- **Information about storage in one common storage facility:** Not required
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Storage class 3**
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Components with critical values that require monitoring at the workplace:**

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppmLong-term value: 999 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm

- **Additional information:** The lists that were valid during the compilation were used as basis.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 3)

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures** Wash hands during breaks and at the end of the work.

· **Breathing equipment:**

Use breathing protection in case of insufficient ventilation.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· **Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

· **Eye/face protection** Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Liquid

· **Colour:**

Colourless

· **Smell:**

Solvent-like

· **Odour threshold:**

Not determined

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

>78 °C

· **Flammability**

Highly flammable.

· **Lower:**

2 Vol %

· **Upper:**

19 Vol %

· **Flash point:**

13 °C (DIN EN ISO 3679)

· **Auto-ignition temperature:**

370 °C

· **Decomposition temperature:**

Not determined

· **pH**

Not determined

· **Viscosity:**

· **Kinematic viscosity at 20 °C**

15 s (DIN 53211/4)

· **dynamic:**

Not determined

· **Solubility**

· **Water:**

Not miscible or difficult to mix

· **Partition coefficient n-octanol/water (log value)**

Not determined

· **Steam pressure at 20 °C:**

57 hPa

Not determined

· **Density and/or relative density**

· **Density at 20 °C**

0.819 g/cm³ (Dichtekugel 10ml 20°C)

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 4)

· Relative density	Not determined
· Vapour density	Not determined
· Particle characteristics	not applicable, as liquid
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· VOC (EU)	See information on Directive 2004/42/EC on the label.
· Change in condition	
· Evaporation rate	Not determined
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	51 mg/l (rat)

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 5)

	LC50/24h	11,200 mg/l (fish)
67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)
123-86-4 n-butyl acetate		
Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Primary irritant effect:**
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

64-17-5 ethanol

EC10/72h	11.5 mg/l (algae)
EC50/24h	858 mg/l (whereas)

- **12.2 Persistence and degradability**

64-17-5 ethanol

OECD Guideline 301B	97 % (not specified)
---------------------	----------------------

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 6)

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT (vapour pressure at 50°C not more than 110 kPa) PAINT
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	 · Class 3 Flammable liquids. · Label 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, S-E B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 13 (replaces version 12)

Revision: 14.07.2026

Product name PrimaSeal Plus

(Contd. of page 7)

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P5c** FLAMMABLE LIQUIDS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· National regulations****· Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.

GB